

Rig 201

DDE SL2500T-AC-3P-650T

Mast

Type	Cantilever Blocks	
Raising method	API 4F, 4th Edition	
Design Compliance		
Ambient temperature design	-40°C thru +45° C	
Static HL Capacity, 12 Lines	600	(544)
Clear working height, feet (mm)	154	(47090)
Width at base, feet (mm)	30	(9144)

Crown Block

Design Compliance	Sheaves API 8C, Frame API 4F	
Configuration	Skewed	
Hook Load Capacity, Tons (Metric Tons)	600	(544)
Drilling Line Size, inches (mm)	1,5	(38)
Fastline Sheave, quantity	1	
Fastline Sheave, inches (mm)	72	(1829)
Cluster Sheaves, quantity	6	
Size, inches (mm)	60	(1524)

Substructure

Model Number	SL 600	
Design Compliance	API 4F, 4th Edition	
Ambient temperature design	-40°C thru +45° C	
Type	Parallelogram, slingshot	
Raising method	Winch	
Casing Capacity, Tons (MT)	600	(544)
Setback Capacity, Tons (MT)	385,8	(350)
Floor Height	33	(10000)
Clear height under rotary beams	27	(8235)

Deadline Anchor

Design Compliance	API 8C	
Drum diameter, inches (mm)	31	(787)
Clamp assembly, inches (mm)	1,5	(38)
Mounting	Leg	
Deadline load rating, lbs (kg)	130000	(58968)
Load Cell Type	Compression	

Traveling Block

Design Compliance	API 8C	
Capacity, Tons (Metric Tons)	600	(544)
Drilling Line Size, inches (mm)	1,5	(38)
Sheaves, number	6	
Size, inches (mm)	60	(1524)